



GB00/02224



PCT/GB CO/02224



INVESTOR IN PEOPLE

ACKNOWLEDGEMENT RECEIPT
DATE: 27 JUL 2000
WIPO PCT

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.


Signed

Dated 22 June 2000

**PRIORITY
DOCUMENT**

SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

Patents Form 1/77

Patents Act 1977
(Rule 16)The
Patent
Office18JUN99 E455616-1 D02893
P01/7700 0.00 - 9914186.3

The Patent Office

Cardiff Road
Newport
Gwent NP9 1RH**Request for grant of a patent**

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

1. Your reference

1650

2. Patent application number

(The Patent Office will fill in this part)

9914186.3

18 JUN 1999

3. Full name, address and postcode of the or of each applicant (*underline all surnames*)Vexcolt (UK) Limited
49 Woolmer way
Woolmer Trading Estate
Bordon
Hampshire GU38 9QE
UK
5662671002
United KingdomPatents ADP number (*if you know it*)

If the applicant is a corporate body, give the country/state of its incorporation

4. Title of the invention

Bridge Joint

5. Name of your agent (*if you have one*)"Address for service" in the United Kingdom to which all correspondence should be sent (*including the postcode*)NIGEL BROOKS CPA
HILL HAMPTON
EAST MEON
PETERSFIELD
HAMPSHIRE GU32 1QNPatents ADP number (*if you know it*)

463001

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (*if you know it*) the or each application number

Country	Priority application number (<i>if you know it</i>)	Date of filing (day / month / year)
GB	NA	NA

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day / month / year)8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (*Answer 'Yes' if:*

yes

- a) any applicant named in part 3 is not an inventor, or
 - b) there is an inventor who is not named as an applicant, or
 - c) any named applicant is a corporate body.
- See note (d))

ts Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form	0
Description	3
Claim(s)	0
Abstract	0
Drawing(s)	1

10. If you are also filing any of the following, state how many against each item.

Priority documents	0
Translations of priority documents	0
Statement of inventorship and right to grant of a patent (Patents Form 7/77)	0
Request for preliminary examination and search (Patents Form 9/77)	0
Request for substantive examination (Patents Form 10/77)	0
Any other documents (please specify)	

11.

I/We request the grant of a patent on the basis of this application.

Signature

Date

18/06/99

12. Name and daytime telephone number of person to contact in the United Kingdom

NIGEL BROOKS CPA (01730) 823647

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

BRIDGE JOINT

The present invention relates to a bridge joint, that is to say a joint between two sections of the roadway of a bridge.

Bridge joints are required primarily because of thermal expansion and contraction in the roadway of a bridge. Also they accommodate initial contract on setting of concrete in the roadway and relative shear and rise/fall of adjacent roadway sections.

The object of the present invention is to provide an improved bridge joint.

A bridge joint according to the invention comprises:

- a number of roadway beams extending laterally of the roadway and including:
 - opposite edge beams adapted to be fixed to respective roadway sections and having support formations and
 - intermediate beams
- a plurality of crossbeams supported at their ends in the support formations of the edge beams, whereby the crossbeams remain mutually parallel as the edge beams move with respect to each other, the crossbeams supporting the intermediate beams and
- spacing features fixed on at least some of the crossbeams and co-operating with the intermediate beams for evenly spacing the latter.

Preferably, the support formations are open, circular section grooves; and the crossbeams have spherical ends which fit the grooves. The crossbeams have a fixed length, whereby their angle with respect to the edge beams is determined by the separation of the edge beams and they are maintained parallel. The grooves may be supplemented by support lips abutting the underside of the crossbeams, particularly where the edge beams are not expected to rise and fall with respect to each other.

Preferably, the spacing features are cams fixed to the crossbeams and acting on the intermediate beams. Whilst it is envisaged that the cams may be fixed to the

top of the crossbeams; in the preferred embodiment, they are fixed to the bottom of the crossbeams. The intermediate beams have apertures through which the crossbeams extend, with the cams acting on bottom portions of the intermediate beams.

5

To help understanding of the invention, a specific embodiment thereof will now be described by way of example and with reference to the accompanying drawing, in which:

Figure 1 is a cross-sectional side view of a bridge joint of the invention; and
10 Figure 2 is an underside view of the bridge joint of Figure 1.

The bridge joint 1 shown in the drawings is set between two adjacent bridge roadway sections 2,3, which are liable to move by a small amount with respect to each other. The joint has steel edge beams 4,5 arranged at the edge of the concrete C
15 of the roadway sections. Each edge beam has a central section 6, which is generally square in cross-section, a horizontal flange 7, which is cast into the concrete and a vertical flange 8, which edges the concrete. The central section has a circular cross-section groove 9, which opens towards the gap G between the roadway sections and the opposite edge beam.

20

Cross beams 10 are regularly spaced along the length of the joint, i.e. across the width of the roadway. They are of square section mild steel tube, with a stainless steel sheath 12 to improve their bearing qualities. To each end of the crossbeams, a spherical steel ball 14 is fixed, as by welding or pinning. The balls are sized to fit in
25 the groove 9. Thus the angle α which the crossbeams make with the edge beams is determined by the fixed length L of the crossbeams between the balls and the variable separation S of the edge beams. Whilst the edge beams remain parallel, the crossbeams will also remain parallel. To maintain the separation of the crossbeams, a number of spacer balls 15 is arranged in each groove 9 between each adjacent pair of
30 crossbeam balls 14.

The crossbeams support a number, three as shown, of intermediate roadway beams 20. They are of general I-beam shape, with small grooves 21 in their heads 22.

The edge flanges 8 of the edge beams also have such small grooves 21. Via these a diaphragm seal 23 is connected between each adjacent pair of roadway beams. These seals exclude water and dirt from the parts of the joint beneath them. The heads of the roadway beams provide the roadway surface between the concrete of the roadway sections 2,3. Feet 24 of the intermediate beams rest on the crossbeams. These transfer road loads to the edge beams via the balls 14 and lips 16 at the lower side of the mouth of the grooves 9.

To maintain the intermediate beams 20 evenly spaced, cams 17 are fixed to the underside of the crossbeams 10. They act against lower extensions 25 of the beams 20, the extensions being fitted to the beams after laying of them on the crossbeams. The joint is thus a coherent structure, which has a variable width. The cams are so shaped as to define a gap therebetween which is the same size as the thickness extensions 25, regardless of the angle α .

The invention is not intended to be restricted to the details of the above described embodiment. For instance the number of intermediate beams can vary. Since the intermediate roadway beams are stiff, the cams need not be provided on each crossbeam. The cams can be provided above the crossbeams, acting against the webs of the intermediate beams, if there is insufficient space for them to act against the beams' feet. For applications where little relative rise/fall is expected, the balls can be replaced by short studs, with flat bottoms bearing against flat bottoms to the grooves in the edge beams.

